



UNIVERSITY OF TWENTE.



Fluid-particle simulation using Smoothed Particle Hydrodynamics and Discrete Element Method (SPH-DEM)

Martin Robinson¹ Stefan Luding¹ and Marco Ramaioli²






1&2 **PARDEM**



Fluid-particle simulation using Smoothed Particle Hydrodynamics and Discrete Element Method (SPH-DEM)

1. **Fluid-particle systems** are ubiquitous in nature and industry
 - Geophysical – e.g. Sediment transport, erosion, avalanches, dam or levee failure.
 - Industry – e.g. food and powder mixing, fluidized bed reactors
2. Development of **meshfree** fluid-particle simulation method:
 - Smoothed Particle Hydrodynamics and Discrete Element Method (SPH-DEM)
3. Applied to:
 - **Validation test** cases using single/multi particle sedimentation
 - **Dispersion of granular bed** by liquid jet – collaboration with Nestle

Fluid-particle simulation – which length scale?



Van der Hoef, M. A., van Sint Annaland, Deen, N. G., & Kuipers, J. A. M. (2008). Numerical simulation of dense gas-solid fluidized beds: A multiscale modeling strategy. *Annual Review of Fluid Mechanics*, 40 (1), 47-70.

UNIVERSITY OF TWENTE.

Fluid Equations – Locally Averaged Navier Stokes Equations

- Anderson and Jacksons (1967) derived locally averaged Navier Stokes equations (AVNS)
- Solid particle distribution is converted to a smooth porosity field

$$\frac{\partial(\varepsilon\rho)}{\partial t} + \nabla \cdot (\varepsilon\rho\mathbf{u}) = 0$$

$$\varepsilon\rho\left(\frac{\partial\mathbf{u}}{\partial t} - \mathbf{u} \cdot \nabla\mathbf{u}\right) = -\nabla P + \nabla \cdot \boldsymbol{\tau} - n\mathbf{f}_i + \varepsilon\rho\mathbf{g}$$

UNIVERSITY OF TWENTE.

Fluid Equations – Locally Averaged Navier Stokes Equations

- Anderson and Jacksons (1967) derived locally averaged Navier Stokes equations (AVNS)
- Solid particle distribution is converted to a smooth porosity field

$$\frac{\partial(\bar{\rho})}{\partial t} + \nabla \cdot (\bar{\rho}\mathbf{u}) = 0$$

$$\bar{\rho} \left(\frac{\partial \mathbf{u}}{\partial t} - \mathbf{u} \cdot \nabla \mathbf{u} \right) = -\nabla P + \nabla \cdot \boldsymbol{\tau} - n\mathbf{f}_i + \bar{\rho}\mathbf{g}$$



Define a
superficial
density

$$\bar{\rho}_a = \varepsilon_a \rho_a = \sum_b m_b W_{ab}$$

UNIVERSITY OF TWENTE.

AVNS-SPH equations

- Substitute normal SPH density with superficial density

$$\frac{d\bar{\rho}_a}{dt} = \sum_b m_b \mathbf{v}_{ab} \cdot \nabla W_{ab}$$

$$\frac{d\mathbf{v}_a}{dt} = -\sum_b m_b \left(\frac{P_a}{\bar{\rho}_a^2} + \frac{P_b}{\bar{\rho}_b^2} + \Pi_{ab} \right) \nabla_a W_{ab} + \frac{\mathbf{f}_a}{m_a}$$


- Reference density for each particle scaled by porosity
- Smoothing length h varies with superficial density

$$P_a = B_a \left(\left(\frac{\bar{\rho}_a}{\varepsilon_a \rho_0} \right)^\gamma - 1 \right) \quad B_a = \frac{100 \varepsilon_a \rho_0 v_m^2}{\gamma} \quad h_a = \sigma \left(\frac{m_a}{\bar{\rho}_a} \right)^{1/d}$$

UNIVERSITY OF TWENTE.


Variable resolution fluid solver

- SPH resolution (smoothing length h) depends on density
- Therefore, resolution coupled to porosity ($h \approx \varepsilon^{-1/3}$)
- Retains accuracy, as particles increase effective viscosity and inhibits turbulent flow



UNIVERSITY OF TWENTE.

Solid phase - Discrete Element Method (DEM)



- Lagrangian method for simulating granular material
- Newton's equations of motion integrated for individual particles

$$m_i \frac{d^2 \mathbf{r}_i}{dt^2} = \sum_j \mathbf{c}_{ij} + \mathbf{f}_i + m_i \mathbf{g}$$

- Contacts modeled using explicit forces \mathbf{c}_{ij}
 - We use a linear spring contact force (with dissipation)
- Coupled to fluid via drag force model \mathbf{f}_i

UNIVERSITY OF TWENTE.


Fluid-Particle Drag Force

- Force on DEM particle due to fluid:

$$\mathbf{f}_i = V_p (-\nabla P + \nabla \cdot \boldsymbol{\tau}) + \mathbf{f}_d$$

- Where \mathbf{f}_d is the drag force model
 - Stokes drag (creeping flow, single particle)
 - Di Felice (1994) drag model (higher Re, multiple particles)

- Drag force calculated on each DEM particle
- Particle drag force then interpolated to surrounding SPH particles
 - Constructed so **Newton's third law satisfied**




UNIVERSITY OF TWENTE.


3D Sedimentation Test Cases

- Single Particle Sedimentation (SPS)
- Sedimentation of a constant porosity block (CPB)
- Rayleigh Taylor Instability (RTI)

SPS



CPB, RTI



UNIVERSITY OF TWENTE.

Set of Realistic Fluid-Particle Parameters

- Particle properties chosen to match glass beads used in dispersion cell experiments
- Contact law – linear spring dashpot
 - Very low stiffness to speed up calculations
 - particle collisions not important here



UNIVERSITY OF TWENTE.

Property	Value
Density	2500 kg/m ³
Diameter	1x10 ⁻⁴ m
Spring Stiffness	1x10 ⁻⁴ kg/s ²
Damping	0 kg/s

Set of Realistic Fluid-Particle Parameters

- Three different fluids used to provide a range of particle Reynolds Numbers
- Parameters based on air, water and 10% glycerol-water solution



Property	Air	Water	Glycerol-water
Density	1.18 kg/m ³	1000 kg/m ³	1150 kg/m ³
Viscosity	1.86x10 ⁻⁵ Pa·s	8.9x10 ⁻⁴ Pa·s	8.9x10 ⁻³ Pa·s
Re _p	0.65 – 3.19	0.15 – 0.85	0.002 – 0.011

UNIVERSITY OF TWENTE.

Set of Realistic Fluid-Particle Parameters

- Stokes law gives an estimate of the fluid-particle relaxation time scale
- This provides an additional time-step constraint




Property	Air	Water	Glycerol-water
Density	1.18 kg/m ³	1000 kg/m ³	1150 kg/m ³
Viscosity	1.86x10 ⁻⁵ Pa·s	8.9x10 ⁻⁴ Pa·s	8.9x10 ⁻³ Pa·s
Re _p	0.65 – 3.19	0.15 – 0.85	0.002 – 0.011
Relaxation Time	7.5x10 ⁻² s	1.56x10 ⁻³ s	1.56x10 ⁻⁴ s

UNIVERSITY OF TWENTE.

Single Particle Sedimentation (SPS)




- Tested a range of particle Reynolds numbers ($0.01 \leq Re_p \leq 10$) and fluid resolution ($1 \leq h/d \leq 6$)
- SPH-DEM results consistently less than 2% error
- Provided the fluid resolution h is sufficiently coarse vs. particles ($h > 2d$)



UNIVERSITY OF TWENTE.



Sedimentation of a constant porosity block (CPB)

- Reproduces terminal velocity well over a range of porosity ($0.5 \leq \epsilon \leq 1.0$)
- Fluid resolution reduces porosity at CPB edge
- Some errors at high porosity gradients - working with alternate drag calculation to minimize this.




Sedimentation of a constant porosity block (CPB)


- Reproduces terminal velocity well over a range of porosity ($0.5 \leq \epsilon \leq 1.0$)
- Fluid resolution reduces porosity at CPB edge
- Some errors at high porosity gradients - working with alternate drag calculation to minimize this.



Rayleigh Taylor Instability (RTI)



- Compare the motion of lowest DEM particle to the predicted growth of the interface in a two-fluid model of RT (Chandrasekhar, 1961)
- Differences from fluid RT – sedimentation velocity & lower ϵ near boundary
- Good results seen for $Re_p \sim 0.01$ (glycerol-water). Difficulties at higher Re_p .






Rayleigh Taylor Instability (RTI)

- Compare the motion of lowest DEM particle to the predicted growth of the interface in a two-fluid model of RT (Chandrasekhar, 1961)
- Differences from fluid RT – sedimentation velocity & lower ϵ near boundary
- Good results seen for $Re_p \sim 0.01$ (glycerol-water). Difficulties at higher Re_p .



Realistic simulation of powder dispersion by a liquid jet

- The dispersion of grains by a liquid jet of interest to food processing industry (Nestlé)
- Experimental (camera, pressure sensor & MRI) data available* for poppy seeds and glass beads dispersed in water
- Goals:
 1. Validate SPH-DEM results to experiments
 2. Investigate dynamics of dispersed bed
 3. Map process parameters to different dynamical regimes



*Courtesy Dr Marco Ramaoli & Chloe Trarieux

Parameters


Name	Symbol	Value
Cell radius	R	11.5 mm
Cell height	H	31 mm
Inlet radius	R_i	0.5 mm
Inlet radius (simulated)	R_{is}	1.9 mm
Inlet flow rate	F_i	100 ml/min
Inlet velocity	V_i	$(1e^{-06} * F_i) / (60\pi R_i^2) = 2.12 \text{ m/s}$
Fluid density	ρ	997 kg/m ³
Fluid viscosity	μ	8.93 Pa·s
Particle diameter	d	1.10 mm (change to 2.2mm)
Particle density	ρ_p	1160 kg/m ³

UNIVERSITY OF TWENTE.

Two initial conditions...


- Wet

1. Cylinder filled with water.
2. Particles allowed to settle (mass*3)
3. Particle mass reset to input parameter
4. Jet starts




- Dry

1. Particles allowed to settle
2. Jet starts




UNIVERSITY OF TWENTE.

Wet Start




UNIVERSITY OF TWENTE.

Wet Start




Dry Start



UNIVERSITY OF TWENTE.



Dry Start



Realistic simulation of powder dispersion by a liquid jet

- Initial results:

- Wet** – Recovers some qualitative features from experiment. Correcting inlet/outlet condition and exploring parameter space
 - Dry** – Fails to recover some major features (eg. Bed lift). Surface tension effects important but not modelled.



UNIVERSITY OF TWENTE.

**Thank you for your attention.
Questions....?**

UNIVERSITY OF TWENTE.